

ELECTRICAL SPECIFICATIONS (OUTPUT)

Max DC Output Power Rating	60KW,120KW,180KW
DC Output Voltage	150 – 1000 Vdc
Outlet Current	CCS2
Charge Ports	2
DC Charging Protocol	DIN 70121
Power Factor	>0.99
THDi	<0.5%
Efficiency	>95% (Peak)
Standby Power	50W*N (Plug)

ELECTRICAL SPECIFICATIONS (INPUT)

Input Voltage Range	400 Vac +/- 15%
Input AC Power rating (Max)	110A, 220A, 330A
Rated Frequency	50Hz or 60Hz
Connector Types	3P + N + PE

MECHANICAL SPECIFICATIONS

Dimensions (L*W*H)	750 * 630 *1912mm
Weight	≤438 kg
Cable Length	5 meters

ENVIRONMENTAL SPECIFICATIONS

Installation Location	Outdoor
Enclosure Protection Rating	IP55 and IK10(cabinet) / IK8(touch screen)
Operating & Storage Temperature	-30° C to +55° C

NETWORK & USER INTERACTION

Network Connections	4G LTE, Ethernet
Communications	OCPP 1.6 JSON
User Interface Screen	7" LCD touch screen
Payment Methods Accepted	RFID, APP